# 

### Complies with the machinery directives 2006/42/EC



NB: Please ensure that the safety instructions have been fully read and understood before initial use of the VWBG-V bolt-on lifting point. Failure to do so may result in serious injuries and/or material damage and eliminates manufacturers warranty.

### **User Instructions - Part 1**

### Safety instructions

This safety instruction/declaration of the manufacturer must be kept on file for the lifetime of the product.

ATTENTION: Please inspect all components prior to use. Damaged, incorrect assembly or improper use may result in serious injuries and/or material damage.

### EC-Declaration of the manufacturer

According to the Machinery Directive 2006/42/EC, annex II B and amendments.

We hereby declare that the design and construction of the equipment detailed within this document, adheres to the appropriate level of health and safety of the corresponding EC regulation.

Any un-authorised modification and/or any incorrect use of the equipment not adhered to within these user instructions waivers this declaration invalid.

The equipment must be regularly tested and inspected as per BGR 500. Failure to carry out the recommended maintenance and testing waivers this declaration invalid.

### Designation of the equipment:

### Type: Hoist Ring for Bolting Vario VWBG-V

Manufacturer's mark: 🕅

Drawings (iges, dxf and step), product information and other support material can be downloaded from www.rud.com.au.

	EC-Declaration of	conformity								
According to the E	C-Machinery Directive 2006	6/42/EC, annex II A and amendments								
Manufacturer: RUD Ketten Rieger & Dietz GmbH u. Co. KG Friedensinsel 73432 Aalen										
We hereby declare that the as mentioned below, corresphealth of the corresponding mentioned harmonized and In case of any modification of tion becomes invalid.	equipment sold by us becau bonds to the appropriate, ba EC-Machinery Directive 200 national norms as well as te of the equipment, not being	use of its design and construction, asic requirements of safety and 06/42/EC as well as to the below chnical specifications. agreed upon with us, this declara-								
Product name:	Load ring									
	VWBG-V / VWBG									
The following harmonized no	rms were applied: EN 12100 : 2011-03 EN 1677-4 : 2009-03	EN 1677-1 : 2009-03								
The following national norms	and technical enecifications	were applied:								
The following national forms	BGR 500, KAP2.8 : 2008-04									
Authorized person for the co	nfiguration of the declaration of the declaration of Reinhard Smetz, RUD Ket	locuments: ten, 73432 Aalen								
Aalen, den 27.06.2014	<u>DrIng. Arne Kriegsmann.</u> Name, function and signature	(Prokurist/QMB) free free free free free free free fre								



### **User Instructions - Part 2**

### 1. Safety Instructions



ATTENTION: Please inspect all lifting points prior to use. Damage, incorrect assembly or improper use may result in serious injuries and/or material damage.

- Not suitable for permanent turning operations under load. Lifting point cannot be turned to 90° from the bolt-on direction under full load.
- The ball bearing must not be disassembled.
- The load ring must not be free to articulate.
- RUD VWBG-V lifting points must only be used by instructed and competent persons considering BGR 500 / DGUV 100-500 and outside Germany noticing the country specific statutory regulations.

### 2. Intended use of VWBG-V

RUD VWBG-V lifting points must only be used for the assembly at the load or at lifting means.

They are intended to be bolted into the payload and can be turned under load, but not under full load, especially not in the  $90^{\circ}$  direction. Not suitable for permanent turning operations under load.

RUD VWBG-V lifting points can also be used as lashing points to attach lashing means.

If the lifting points are used exclusively for lashing the value of the WLL (working load limit) can be doubled. LC (lashing capacity) =  $2 \times WLL$ .

RUD VWGB-V lifting points must only be used in the hereby described operation purpose.

Before installing and every use, visually inspect RUD lifting points, with particular attention to any evidence of corrosion, wear and weld cracks and deformations. Please ensure compatibility of bolt thread and tapped hole.

#### 3. Assembly and Instruction Manual

#### **3.1 General Information**

• Temperature range:

Usage at higher temperatures is not recommended due to the grease filling in the ball bearing. Should this though be necessary, the working load limit (WLL) of the VWBG-V must be reduced as follows:

-40°C up to 100°C	no reduction
100°C up to 200°C	minus 15 %
200°C up to 250°C	minus 20 %
250°C up to 350°C	minus 25 %

#### Temperatures exceeding 350°C are prohibited!

Please pay attention when using DIN EN 7042 (DIN 980) nuts the max. operation temperature of 150°C (acc. to DIN EN ISO 2320).

• RUD VWBG-V lifting points must not be used with aggressive chemicals such as acids, alkaline solutions and their vapours.

#### 3.2 Hints for the assembly

 The material construction to which the lifting point will be attached should be of adequate strength to withstand forces during lifting without deformation. The German testing authority BG, recommends the following minimum for the bolt lengths:

1.0 x M in steel (minimum quality S235JR [1.0037])  $\approx$  AS3678 GR250.

1.25 x M (thread diameter) in cast iron (e.g. GG 25)

2 x M (thread diameter) in aluminium

2.5 x M (thread diameter) in light alloys of low strength (M = thread size/diameter, e.g. M20)

- When lifting light metals, nonferrous metals and gray cast iron the thread has to be chosen in such a way that the WLL of the thread corresponds to the requirements of the base material.
- The min. quality of the hexagon bolt of the VWBG-V must be class 10.9 according to EN 24014 (DIN 931) with correct nominal diameter.
- RUD supplies the Vario length complete with a washer and crack-detected nut corresponding to DIN EN ISO 7042 (DIN 980) or will be supplied with a crack inspected collar nut acc. to DIN 6331 or 2 x crack inspected hex nuts Class 8 AS1112.1 with washer.
- The position of the lifting points must be carried out in such a way that unintended movement like turning or flipping will be avoided.
  - For single leg lifts, the lifting point should be vertically above the centre of gravity of the load.
  - For two leg lifts, the lifting points must be equidistant to/ or above the centre of gravity of the load.
  - For three and four leg lifts, the lifting points should be arranged symmetrical around the centre of the gravity, in the same plane if possible.

**Load Symmetry:** The working load limit of individual RUD lifting points are calculated using the following formula and are based on symmetrical loading:

		WLL	= required of lifting point/individual leg (kg)						
WLL =	G	G	= load weight (kg)						
	n x cos ß	n	= number of load bearing legs						
		ß	= angle of inclination of the individual leg						

### NOTE: For WLL Calculations



ß angle is taken from the vertical plane.
Included angle is the angle between the sling legs.

Number of load bearing legs is as follows:

	Symetrical	Unsymetrical
2/3/4 leg	2	1

Load bearing legs (compare also with table 1)

- When lifting points are used in a multileg assembly, care should be taken to calculate the WLL (Working Load Limit) due to the deration caused by forces acting in multiple directions. The reduction in WLL (Working Load Limit) for multileg assemblies should be checked with relevant Standards e.g. AS 3775.2:2014 Chain slings for lifting purposes - Grade T(80) and V(100) - Care and use.
- The lifting points should be mounted in such a way that they may easily be accessed for inspection and assembly/ disassembly of the sling.

# 

### User Instructions - Part 2

- A plane bolting surface must be guaranteed to ensure correct mating of the lift compoment. The thread must be carried out acc. to DIN 76 (countersink max. 1.05xd).
- Tapped holes must be machined deep enough so that the bearing surface of the lifting point will be supported. Machine through holes up to DIN EN 20273-middle.
- For single use just tighten with spanner. For long term application and when turning loads the VWBG-V should be tightened to torque according to relevant table (+/- 10%). In case of turning movements (continuous operation) the recommended torques have to be checked regulary.
- The type VWBG-V can be supplied with different thread lengths (see Fvario in table 2), and the metric versions with washer and crack detected nut.



ATTENTION: Check the correct assembly (see chapter 4, Inspection Criteria).

### 3.3 User Instructions

• Check frequently and before each initial operation the whole lifting mean for corrosion, wear, deformation etc. (see chapter 4, Inspection criteria).



ATTENTION: Incorrectly assembled or damaged lifting points, as well as improper use can lead to injuries to persons and plant damage. Please inspect all lifting points before each use.

 VWBG-Vs are suitable for turning and flipping of loads. In doing so, all positions of the ring can occur. The stated WLL at the lifting point is given for the most inappropriate possible case of operation (see picture 5 - part X). When ring has been adjusted manually (see picture Y) the higher (WLL) values from table 3 can be used.



ATTENTION: Pay attention during the usage that the load type will not be changed.

If the VWBG-V is to be loaded only perpendicular (in axial direction of the thread, see picture 3 - part Z) the corresponding WLL values from table 3 (inclination angle  $0^{\circ}$ ) can be used.

 The ring of the manually adjusted VWBG-V can be pivoted by approx. 230° (see picture 1).





#### ATTENTION: The lifting ring must rotate and pivot without interference during lifting (see picture 2).

- When lifting means (sling chains) are hinged or unhinged, no pinching, shearing or joint spots must occur during the handling. Avoid damage of lifting means resulting from sharp edges.
- Distance yourself from the direct danger zone.
- · Always watch the load during the lift.
- Avoid sudden or shock loading.



ATTENTION: Loading or vibration can lead to unintentional loosening.



Pic. 2: Forbidden contact or support at/or with edge

 To prevent unintentional dismounting through shock loading, rotation or vibration thread loking fluid such as Loctite (depending on the application, please refer to the manufacturer's instruction) should be used to secure the bolt.

### 3.4 Hints for regular inspection

After fitting, an annual inspection (or sooner if conditions dictate) should be carried out by a competent person examining for continued suitability. Also inspect after damage and special occurance.

# 

### **User Instructions - Part 2**

### 4 Inspection criteria

Observe and control the following points before each initial operation at regular time intervals, after the assembly and after special incidents:

- · Correct bolt- and nut size plus thread engagement.
- Inspection of bolting torque.
- The bearing surface of the VWBG-V must be plane.
- · Completeness of the lifting point.
- · Complete readable WLL markings and manufacturer sign.
- Deformation at load bearing components e.g. base body, load ring and threaded bolt.
- Mechanical damage, like notches, especially in areas ٠ where tensile stress occurs.
- · Locking screw at the side must be tightened.
- Reduction of cross-section due to wear >10 % or when the wear marks have been reached in the main load bearing directions.
- · Cracks or any other damage.
- · Function and damage of bolt threads and nuts.
- Smooth rotation between upper and base part of the VWBG-V must be guaranteed.
- The maximum gap "S" between upper and base part must not be exceeded:

VWBG-V 0.3 - 0.45: max. 1.2 mm VWBG-V 0.6 - 2.0: max. 1.5 mm VWBG-V 3.5 - 5.0: max. 3.0 mm



### Pic. 3: Distance between upper and base part plus bearing wear groove

### 5 Hints for the Repairing

Repair work must only be carried out by a competent person at RUD or by a RUD trained and authorised service station, which has obtained the necessary knowledge and skills.

RUD-VWBG-V's are designed for a dynamical loading of 20.000 load cycles at nominal working load. The BG recommends: At a high dynamic loading with high numbers of load cycles (continious work) the bearing stress acc. to FEM group 1Bm (M3 acc. to DIN 818-7) must be reduced.

### Example to investigate the required thread length F vario:

Plate thickness 50 mm, through hole for M 20 bolt, height of nut 20 mm, thickness of the washer 3mm, plus bolt projection 5 mm (2x pitch).

Order length: VWBG-V-2.0 M 20 x 78.

# 

### **User Instructions - Part 3**

\* **—** X



Nominal WLL (worst case scenario)

Pic. 4: Loading directions



Manual adjustment (higher values in brackets possible depending on usage)



Vertical loading (WLL acc. to chart)

Method of lifting	9	¢ G	A G G	G	G	β¢ G	β, G	β, G
Number of Legs	3	1	2	1	2	2/3/4	2/3/4	2/3/4
Load Direction		0°	0°	90 °	90 °	60°	90°	120°
Туре	Thread							
WWBG-V 0.3	M8 / <sup>5</sup> / <sub>16</sub> "	0.6	1.2	0.3 (0.4)	0.6 (0.8)	0.52 (0.69)	0.42 (0.56)	0.3 (0.4)
VWBG-V 0.45	M10 / <sup>3</sup> / <sub>8</sub> "	0.9	1.8	0.45 (0.6)	0.9 (1.2)	0.78 (1.0)	0.63 (0.85)	0.4 (0.6)
VWBG-V 0,6	M12 / 1/2"	1.2	2.4	0.6 (0.7)	1.2 (1.5)	1.0 (1.3)	0.85 (1.1)	0.6 (0.7)
VWBG-V 1.0	M14	2.0	4.0	1.0 (1.25)	2.0 (2.5)	1.73 (2.2)	1.4 (1.8)	1.0 (1.25)
VWBG-V 1.3	M16 / <sup>5</sup> / <sub>8</sub> "	2.6	5.2	1.3 (1.5)	2.6 (3.0)	2.2 (2.6)	1.8 (2.1)	1.3 (1.5)
VWBG-V 1.8	M18	3.6	7.2	1.8 (2.0)	3.6 (4.0)	3.1 (3.5)	2.5 (2.8)	1.8 (2.0)
VWBG-V 2.0	M20 / <sup>3</sup> / <sub>4</sub> "	4.0	8.0	2.0 (2.5)	4.0 (5.0)	3.5 (4.3)	2.8 (3.5)	2.0 (2.5)
VWBG-V 2.0	M22	4.0	8.0	2.0 (2.5)	4.0 (5.0)	3.5 (4.3)	2.8 (3.5)	2.0 (2.5)
VWBG-V 3.5	M24 / 1"	7.0	14.0	3.5 (4.0)	7.0 (8.0)	6.1 (6.9)	4.9 (5.6)	3.5 (4.0)
VWBG-V 5.0	M27	7.0	14.0	3.5 (4.0)	7.0 (8.0)	6.1 (6.9)	4.9 (5.6)	3.5 (4.0)
VWBG-V 5.0	M30 / 1 <sup>1</sup> / <sub>4</sub> "	10.0	20.0	5.0 (6.0)	10.0 (12.0)	8.7 (10.4)	7.1 (8.4)	5.0 (6.0)

Table 1: WLL-overview VWBG-V



NOTE: The VWBG-V is designed to rotate and turn the load. Therefore the lifting point can engage in any position. The WLL is embosed for the worst case situation in which the load direction may occur (see picture X). The ring can be manually adjusted to the direction of pull (see picture Y). Then the values in the brackets can be used.

# 

### **User Instructions - Part 3**



Pic. 5: Dimensioning VWBG-V (standard)



Pic. 6: Dimensioning VWBG-V (vario)

Туре	WLL [t]	A [mm]	B [mm]	C [mm]	D [mm]	Fstand [mm]	Fmax [mm]	G [mm]	K [mm]	M [mm]	T [mm]	x	weight [kg/ pc.]	Bolting Torque [Nm]	RefNo. Stand.	RefNo. Vario with washer and nut
VWBG-V 0.3 M8	0.3 (0.4)	8	31	29	30	13	102	36	28	8	76	18	0.25	10	7103720	8600330
VWBG-V 0.45 M10	0.45 (0.6)	8	31	29	36	17	122	38	30	10	78	19	0.3	10	7103715	8600331
VWBG-V 0.6 M12	0.6 (0.7)	10	49	35	42	21	140	47	36	12	107	19	0.4	10	7100180	8600332
VWBG-V 1.0 M14	1.0 (1.25)	13	46	38	48	21	65	56	41	14	113	-	0.6	25	-	8600337
VWBG-V 1.3 M16	1.3 (1.5)	13	46	38	48	25	180	56	41	16	113	28	0.6	30	7100430	8600333
VWBG-V 1.8 M18	1.8 (2.0)	13	54	35	62	27	83	67	55	18	137	-	1.1	50	-	8600338
VWBG-V 2.0 M20	2.0 (2.5)	13	54	35	62	33	223	67	55	20	137	30	1.4	70	7100800	8600334
VWBG-V 2.0 M22	2.0 (2.5)	13	54	35	62	33	94	64	55	22	137	-	1.5	120	-	8600334
VWBG-V 3.5 M24	3.5 (4.0)	18	66	40	81	40	255	88	70	24	173	25	2.6	150	7100640	8600335
VWBG-V 3.5 M27	3.5 (4.0)	18	66	40	81	40	92	88	70	27	173	-	2.9	200	-	8600335
VWBG-V 5.0 M30	5.0 (6.0)	22	90	50	99	50	330	106	85	30	221	32	5.5	225	7100650	8600336

Table 2: Dimensioning (metric)

Туре	WLL [t]	A [mm]	B [mm]	C [mm]	D [mm]	F [mm]	G [mm]	K [mm]	M [mm]	T [mm]	weight [kg/pc]	Bolting- torque [Nm]	RefNo. Stand.
VWBG-V 0.3 - <sup>5</sup> / <sub>16</sub> " - 18 UNC	0.3 (0.4)	8	31	29	30	13	36	28	<sup>5</sup> / "	76	0.25	10	7991090
VWBG-V 0.45 - <sup>3</sup> / <sub>8</sub> " - 16 UNC	0.45 (0.6)	8	31	29	36	17	38	30	<sup>3</sup> / <sub>8</sub> "	78	0.3	10	7991091
VWBG-V 0.6 - 1/2" - 13 UNC	0.6 (0.7)	10	49	35	42	21	47	36	1/2"	107	0.4	10	7991092
VWBG-V 1.3 - 5/8" - 11 UNC	1.3 (1.5)	13	46	38	48	29	56	41	<sup>5</sup> / <sub>8</sub> "	114	0.6	30	7991093
VWBG-V 2.0 - <sup>3</sup> / <sub>4</sub> " - 10 UNC	2.0 (2.5)	13	54	35	62	29	67	55	<sup>3</sup> / <sub>4</sub> "	137	1.4	70	7991094
VWBG-V 3.5 - 1" - 8 UNC	3.5 (4.0)	18	66	40	81	40	88	70	1"	173	2.6	150	7991095
VWBG-V 5.0 - 11/4" - 7 UNC	5.0 (6.0)	22	90	50	99	48	106	85	1 <sup>1</sup> / <sub>4</sub> "	221	5.5	225	7991096

Table 3: Dimensioning VWBG-V\*



Head Office: Brisbane 12 Commerce Place, Larapinta QLD 4110 p 07 3809 1300 f 07 3809 1301

info@rud.com.au

Perth Office 107 Broadway, Bassendean WA 6054 p 08 6278 1788 f 08 6278 4788



www.rud.com.au