

GEARED TROLLEY

Global Geared Trolleys feature the highest quality manufacturing against a very competitive price. Complying to the Australian 4991 standard.





FEATURES

- All Global models are manufactured to comply with AS4991
- o Fully adjustable to suit various beam widths
- Fitted with anti-drop plates for improved safety and compliance
- o High-grade, fully sealed bearings for maintenance free extended life

SPECIFICATIONS

Model	GLGT050	GLGT100	GLGT200	GLGT300	GLGT500
Rated Capacity (Kg)	500	1,000	2,000	3,000	5,000
Test load (Kg)	750	1,500	3,000	4,500	7,500
Beam width range (mm)	50-152	64-203	88-203	100-203	114-203
Pin configuration	Single	Single	Single	Single	Single
Min. radius of curve (m)	0.8	1.0	1.1	1.3	1.4
Net weight (Kg)	10.5	14.5	21.5	31.0	46.0





DIMENSIONS

Model	GLGT050	GLGT100	GLGT200	GLGT300	GLGT500		
A	223	270	300	356	405		
В	188	224	261	308	354		
С	32	40	52	62	75		
D	24	30	38	40	50		
G	1.5 – 3.0						
E	273	341	349	362	374		
Н	105	127	146	169	197		
1	31	38	36	40	42		
F	50 - 152	64 - 203	88 - 203	100 - 203	114 – 203		