



- Quenched and Tempered Alloy Steel.
- At least 25% greater WLL than traditional G80 products.
- Manufactured in accordance with EN 1677- 2 and ASME B30.26, ASME B30.10, PAS1061.
- Certified by DGUV GS-OA-15-05 & DGUV GS-MO-15-05
- Proof Load tested at 2.5 times the WLL with certification for each batch manufactured.
- Design Factor 4:1.
- Fatigue rated to 20,000 cycles at 1.5 times the WLL.
- Tempering temperature minimum 400°C
- Magnaflux crack detection is performed 100% on each batch.



8-P044
Repair kit available

G-100 Eye Sling Hook

with Latch

| Item No. | For Grade 100 Chain | WLL tonnes* | Dimensions (mm) | | | | | | N.W. kg |
|------------|---------------------------|----------------|-----------------|----|----|-----|-----|----|------------|
| | mm | | A | D | H | K | P1 | T | |
| X-044/S-06 | 6 | 1.4 | 20 | 10 | 19 | 80 | 23 | 17 | 0.3 |
| X-044/S-07 | 7,8 | 2.5 | 25 | 12 | 23 | 98 | 28 | 20 | 0.5 |
| X-044/S-10 | 10 | 4.0 | 32 | 15 | 31 | 121 | 36 | 23 | 1.0 |
| X-044/S-13 | 13 | 6.7 | 40 | 18 | 38 | 152 | 40 | 27 | 1.8 |
| X-044/S-16 | 16 | 10.0 | 50 | 22 | 45 | 185 | 44 | 32 | 3.4 |
| X-044/S-20 | 20 | 16.0 | 61 | 27 | 64 | 230 | 54 | 48 | 7.3 |
| X-044/S-22 | 22 | 19.0 | 51 | 31 | 63 | 245 | 76 | 52 | 9.3 |
| X-044/S-26 | 26 | 26.5 | 65 | 35 | 80 | 279 | 77 | 60 | 13.5 |
| X-044/S-32 | 32 | 40.0 | 88 | 40 | 86 | 352 | 114 | 65 | 22.0 |

★ Design factor 4:1 proof tested and certified.