


## TiTAN G80 LIFTING CHAIN (AS2321)




Code	Chain Size	d	tol.	p	tol.	W	tol.	WLL (t)	Weight p/m (kg)
TCG8B-6	6mm	6	0.2	18.2	0.7	21	0.6	1.2	0.86
TCG8B-8	8mm	8	0.2	24	0.6	27.5	0.7	2	1.49
TCG8B-10	10mm	10	0.2	30	0.6	34.5	0.7	3.2	2.31
TCG8B-13	13mm	13	0.2	39	0.7	45	0.8	5.3	3.87

## TiTAN G80 SINGLE RINGS C/W FLATS



### FEATURES

- Single oblong links allow flexibility in the construction of single or double chain slings including wire rope slings
- Comes with flat section
- Forged super alloy steel - quenched and tempered
- Suitable for EN818 G80 chains
- Complies with AS3776/EN1677
- Individually proof tested at 2 times WLL
- Fatigue tested at 1.5 x WLL for 20000 cycles
- 100% Magnaflux crack detection
- Yellow powder plastified finish
- Test certificates available




Code	1-leg sling	2-leg sling	Weight (kg)	WLL (t)	Dimensions (mm)		
					A	B	D
T487SR-87	8	7	0.38	2.6	120	70	13
T487SR-108	10	8	0.67	3.5	140	80	16
T487SR-1310	13	10	1.2	5.5	160	95	20
T487SR-1613	16	13	2.45	9.2	190	110	26
T487SR-2016	20	16	4.48	13.8	230	130	32
T487SR-2220	22	20	7.5	21.6	275	150	38

## TiTAN G80 MULTI RINGS C/W FLATS



### FEATURES

- Master link & 2 intermediate links for 2, 3 or 4 leg chain slings and wire rope slings
- Comes with flat sections on intermediate links
- Forged super alloy steel - quenched and tempered
- Suitable for EN818 G80 chains
- Individually proof tested at 2 times WLL
- Complies with AS3776/EN1677
- Fatigue tested at 1.5 x WLL for 20000 cycles
- 100% Magnaflux crack detection
- Yellow powder plastified finish
- Test certificates available



Code	3 and 4-leg slings	Weight (kg)	WLL (t)	A	B	D	a	b	d
T488MR-08	8	1.9	3.5	160	95	20	110	60	13
T488MR-10	10	2.82	5.5	160	95	22	140	80	16
T488MR-13	13	4.87	9.2	190	110	26	160	95	20
T488MR-16	16	9.38	13.8	230	130	32	190	110	26
T488MR-20	20	15.28	21.6	275	150	38	230	130	30